

# GREENS KING® IV PLUS



## SIMPLY DELIVERS TRUSTED PERFORMANCE

The Greens King IV Plus is a trusted and proven riding greens mower that offers superior quality of cut every time. The Greens King IV Plus, available in both gas and diesel models, features power steering for easy operation and additional horsepower to tackle harder jobs. All Greens King models feature a lightweight, simple design that is gentle on turf and easy to maintain.

**.062 - .438"**  
HEIGHT OF CUT

**GAS  
OR  
DIESEL**

**3.7 MPH**  
MOW SPEED

**62"**  
WIDTH OF CUT



# GREENS KING IV PLUS

## JACOBSEN® ADVANTAGE

For over 95 years, Jacobsen has been designing and manufacturing industry-leading turf maintenance equipment. A strong focus on engineering innovative technology has led to advancements that deliver impeccable quality of cut on user-friendly equipment.



## EQUIPPED AS STANDARD

- Greenscare Biodegradable Oil
- On-Board Backlapping
- Walk-Through Operator Station
- Free-Floating, Steerable Tractor Heads

## OPTIONS

- Vertical Mowers
- Spikers
- Brushes
- Greens rollers
- Turf Groomers® for 3D Mowing
- Full Lineup of Accessories

ENGINE	GAS		DIESEL
<b>TYPE</b>	Briggs & Stratton® Vanguard™ V-twin		Kubota® D722 3-cylinder Tier 4 Gas; Briggs & Stratton® Vanguard™ V-twin
<b>HORSEPOWER*</b>	18 hp (13.4 kW) @3600 rpm		17.7 hp (13.2 kW)
<b>DISPLACEMENT</b>	34.78 cu. in. (570 cc) @3600 rpm		43.88 cu. in. (719 cc)
<b>AIR CLEANER SYSTEM</b>	Dual Element		Dry, two stage
<b>COOLING SYSTEM</b>	Air cooled		Pressurized, sealed cooling system; coolant capacity: 3 qt. (2.85 L)
<b>FUEL CAPACITY</b>	8 gal. (31 L)		8 gal. (31 L)
TRACTION & DRIVE			
<b>TRACTION DRIVE</b>	Hydraulic motor on each drive wheel		
<b>REEL DRIVE</b>	Gear-type hydraulic motor; backlap control valve standard		
<b>REEL LIFT HYDRAULIC SYSTEM</b>	Hydraulic double action cylinders; 5 gal. (18.9 L) capacity; 20-micron, full flow filtration; biodegradable fluid		
SPEED (MAXIMUM)			
<b>MOWING</b>	3.7 mph (6 km/h)		
<b>TRANSPORT</b>	6.6 mph (10.6 km/h)		
<b>REVERSE</b>	3.5 mph (5.6 km/h)		
TIRES, BRAKES & STEERING			
<b>TIRES</b>	18 x 9.5 - 8, 2-ply, pneumatic, tubeless		
<b>PARKING BRAKE</b>	Internal expanding, hand operated		
<b>GROUND PRESSURE</b>	10 psi (0.7 kg/cm <sup>2</sup> )		
<b>STEERING</b>	Power		
REELS & BLADES			
<b>NUMBER &amp; SIZE</b>	Three 22 in. (56 cm) reels; 5 in. (12.7 cm) diameter		
<b>NUMBER OF BLADES</b>	7, 9, 11		
<b>BLADE MATERIAL</b>	Hardened, high-carbon steel		
<b>CUTTING FREQUENCY</b>	0.053 in./mph (0.836 mm/kph) with 11 blade reels, 0.035 in./mph (0.889 mm/kph) with 5 blade reels		
<b>OVERALL CUTTING WIDTH</b>	62 in. (1.6 m)		
<b>HEIGHT-OF-CUT RANGE**</b>	0.062 - 0.438 in. (1.6 - 11.1 mm)		
WEIGHT & DIMENSIONS			
<b>WEIGHT</b>	GK IV Plus Gas: 1073 lbs. (486.7 kg)	GK IV Plus Diesel: 1174 lbs (532.5 kg)	
<b>LENGTH</b> (less catchers)	87.5 in. (2.22 m)		
<b>HEIGHT</b> (with ROPS)	78 in. (1.98 m)		
<b>WHEELBASE</b>	51.5 in. (1.34 m)		
<b>WIDTH</b>	70 in. (1.78 m) in mow mode; 50.5 in. (1.27 m) in transport mode		

\* Engine power is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.  
 \*\* Height of cut depends on turf condition, reel wear and bedknife installed.

NOTE: Specifications, while correct at time of printing, may change without notice.