



CUSHMAN



# HAULER® 4X4

**BUILT TO MAKE YOUR TOUGHEST JOBS EASY**

With its “Let’s Work” attitude the Cushman® Hauler® 4x4 is ready to conquer your most intimidating to-do list. Its four-wheel independent suspension, locking rear differential and impressive 2,000-lb towing capacity makes every task within reach. A range of standard features, including seatbelts, ROPS, and doors, protects your crew from the rigors of the day. With your choice of a quiet 50-hp gas or robust 25-hp diesel engine, watch this powerhouse make light work of your heaviest loads.

**LET’S WORK.®**

**50HP GAS  
OR  
25HP DIESEL**

**1500LB  
LOAD  
CAPACITY**

**2000LB  
TOWING  
CAPACITY**

**14.68 CU. FT.  
BED CAPACITY**



# CUSHMAN® HAULER® 4X4



## STANDARD FEATURES:

- ROPS
- Headrest
- Seatbelts
- Half Doors
- Glove Box
- Multi-Function Display
- 12-Volt Outlet
- All Terrain Tires
- Side Fill Gas Tank
- Headlights
- Taillights
- Brakelights
- Locking Rear Differential
- Horn
- Lower Brushguard

## OPTIONS & ACCESSORIES:

- Power Steering
- Full Windshield with Air Vents
- Glass Windshield
- Canopy
- Center Seat Console
- Underseat Storage
- Rear View Mirror
- Sun Visor
- Grille Guard
- Headlight Guard
- Rear Bumper Kit
- Cab
- Back Up Alarm
- 4500 lb WARN Winch

|                                     | GAS  | DIESEL   |
|-------------------------------------|--|--|
| <b>BODY &amp; CHASSIS</b>           |  |  |
| <b>FRAME</b>                        | Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat | Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat |
| <b>BODY &amp; FINISH</b>            | TPO Molded in Color  | TPO Molded in Color  |
| <b>STANDARD COLOR</b>               | Dynamic Charcoal   | Dynamic Charcoal   |
| <b>DIMENSIONS</b>                   |  |  |
| <b>OVERALL LENGTH</b>               | 126 in (320 cm)  | 126 in (320 cm)  |
| <b>OVERALL WIDTH</b>                | 63 in (160 cm)   | 63 in (160 cm)   |
| <b>OVERALL HEIGHT (WITH CANOPY)</b> | 74 in (188 cm)   | 74 in (188 cm)   |
| <b>WHEEL BASE</b>                   | 85 in (216 cm)   | 85 in (216 cm)   |
| <b>FRONT WHEEL TRACK</b>            | 51 in (129.5cm)  | 51 in (129.5 cm)   |
| <b>REAR WHEEL TRACK</b>             | 51 in (129.5 cm)   | 51 in (129.5 cm)   |
| <b>GROUND CLEARANCE</b>             | 10.75 in (27.4 cm)   | 10.75 in (27.4 cm)   |
| <b>CARGO BOX CAPACITY</b>           | 14.68 cu ft (0.42 cu. m)                                       | 14.68 cu ft (0.42 cu. m)                                       |
| <b>POWER</b>                        |  |  |
| <b>POWERTRAIN</b>                   | Whisper Quiet 50 HP, 812 cc, 4 Stroke Gas Engine               | 25 HP (18.6 kW), 1.03L Liquid Cooled, 3 Cylinder Diesel Engine |
| <b>VALVE TRAIN</b>                  | 3 Cylinder DOHC  | 3 Cylinder   |
| <b>HORSEPOWER (KW)</b>              | 50 HP, (37.3 kW)   | 25 HP, 1028 cc   |
| <b>ELECTRICAL SYSTEM</b>            | 12V, Alternator  | 12V, Alternator  |
| <b>BATTERY (QTY/TYPE)</b>           | One 12-Volt Maintenance Free                                   | One 12-Volt Maintenance Free                                   |
| <b>KEY OR PEDAL START</b>           | Key  | Key  |
| <b>OIL FILTER</b>                   | Automotive, Screw On   | Automotive, Screw On   |
| <b>COOLING SYSTEM</b>               | Liquid with Fan  | Liquid with Fan  |
| <b>FUEL CAPACITY</b>                | 10 gal (37.9 L)  | 10 gal (37.9 L)  |
| <b>DRIVE TRAIN</b>                  | Continuously Variable Transmission (CVT)                       | Continuously Variable Transmission (CVT)                       |
| <b>TRANSAXLE</b>                    | 2/4WD Front, Selectable Locking Rear                           | 2/4WD Front, Selectable Locking Rear                           |
| <b>GEAR SELECTION</b>               | Mechanical, Steering Column Mounted                            | Mechanical, Steering Column Mounted                            |
| <b>FRONT/REAR AXLE RATIO</b>        | 3.1:1  | 3.1:1  |
| <b>PERFORMANCE</b>                  |  |  |
| <b>SEATING CAPACITY</b>             | 3 Person   | 3 Person   |
| <b>CURB WEIGHT</b>                  | 1,657 lb (751.6 kg)  | 1,608 lb (729.4 kg)  |
| <b>BED LOAD CAPACITY</b>            | 1000 lb (453.6 kg)   | 1000 lb (453.6 kg)   |
| <b>VEHICLE LOAD CAPACITY</b>        | 1500 lb (680.4 kg)   | 1500 lb (680.4 kg)   |
| <b>SPEED</b>                        | 25 mph (40.2 kph)  | 25 mph (40.2 kph)  |
| <b>TOWING CAPACITY</b>              | 2000 lb (907.2 kg)   | 2000 lb (907.2 kg)   |
| <b>OUTSIDE CLEARANCE CIRCLE</b>     | 29.5 ft.   | 29.5 ft  |
| <b>STEERING &amp; SUSPENSION</b>    |  |  |
| <b>STEERING</b>                     | Rack and Pinion, Tilt Steering Wheel                           |  |
| <b>FRONT SUSPENSION</b>             | Double A-Arm with 10 in (25.4 cm) Travel                       |  |
| <b>REAR SUSPENSION</b>              | Double A-Arm with 9.5 in (24.1 cm) Travel                      |  |
| <b>SERVICE BRAKE</b>                | Dual Piston Front/Single Piston Rear Calipers                  |  |
| <b>PARKING BRAKE</b>                | Parking Gear, Activated Via Shifter                            |  |
| <b>FRONT/REAR TIRES</b>             | 25 x 10.5 - 12 All Terrain                                     |  |