



**CUSHMAN**



# HAULER® 4x4

**EXCEED YOUR WORK LIMITS**

Built with plenty of muscle, the Cushman® Hauler® 4x4 is equipped to attack your toughest jobs. An impressive 2,000-lb towing capacity, 1,500-lb vehicle payload, four-wheel independent suspension and a top speed of 25 mph, make the Hauler 4x4 ideal for transporting crew and cargo around your facility. Stacked full of standard features including seatbelts, ROPS and doors, your crew will arrive safely, ready to work. With power and performance like that, the Hauler 4x4 makes everything within reach.

**LET'S WORK.®**

**50HP GAS**  
OR  
**25HP DIESEL**

**1500LB**  
LOAD  
CAPACITY

**2000LB**  
TOWING  
CAPACITY

**14.68 CU. FT.**  
BED CAPACITY



# CUSHMAN® HAULER® 4X4



3 PASSENGER SEAT



UNDER SEAT STORAGE



CENTER SEAT CONSOLE



FUNCTIONAL DASH

## STANDARD FEATURES:

- ROPS
- Headrest
- Seatbelts
- Half Doors
- Glove Box
- Multi-Function Display
- 12-Volt Outlet
- All Terrain Tires
- Side Fill Gas Tank
- Headlights
- Taillights
- Brakelights
- Locking Rear Differential
- Horn
- Lower Brushguard

## OPTIONS & ACCESSORIES:

- Power Steering
- Full Windshield with Air Vents
- Glass Windshield
- Canopy
- Center Seat Console
- Underseat Storage
- Rear View Mirror
- Sun Visor
- Grille Guard
- Headlight Guard
- Rear Bumper Kit
- Back Up Alarm
- 4500 lb WARN Winch

	GAS	DIESEL
<b>BODY &amp; CHASSIS</b>		
<b>FRAME</b>	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat
<b>BODY &amp; FINISH</b>	TPO Molded in Color	TPO Molded in Color
<b>STANDARD COLOR</b>	Dynamic Charcoal	Dynamic Charcoal
<b>DIMENSIONS</b>		
<b>OVERALL LENGTH</b>	126 in (320 cm)	126 in (320 cm)
<b>OVERALL WIDTH</b>	63 in (160 cm)	63 in (160 cm)
<b>OVERALL HEIGHT (WITH CANOPY)</b>	74 in (188 cm)	74 in (188 cm)
<b>WHEEL BASE</b>	85 in (216 cm)	85 in (216 cm)
<b>FRONT WHEEL TRACK</b>	51 in (129.5cm)	51 in (129.5 cm)
<b>REAR WHEEL TRACK</b>	51 in (129.5 cm)	51 in (129.5 cm)
<b>GROUND CLEARANCE</b>	10.75 in (27.4 cm)	10.75 in (27.4 cm)
<b>CARGO BOX CAPACITY</b>	14.68 cu ft (0.42 cu. m)	14.68 cu ft (0.42 cu. m)
<b>POWER</b>		
<b>POWERTRAIN</b>	Whisper Quiet 50 HP, 812 cc, 4 Stroke Gas Engine	25 HP (18.6 kW), 1.03L Liquid Cooled, 3 Cylinder Diesel Engine
<b>VALVE TRAIN</b>	3 Cylinder DOHC	3 Cylinder
<b>HORSEPOWER (KW)</b>	50 HP, (37.3 kW)	25 HP, 1028 cc
<b>ELECTRICAL SYSTEM</b>	12V, Alternator	12V, Alternator
<b>BATTERY (QTY/TYPE)</b>	One 12-Volt Maintenance Free	One 12-Volt Maintenance Free
<b>KEY OR PEDAL START</b>	Key	Key
<b>OIL FILTER</b>	Automotive, Screw On	Automotive, Screw On
<b>COOLING SYSTEM</b>	Liquid with Fan	Liquid with Fan
<b>FUEL CAPACITY</b>	10 gal (37.9 L)	10 gal (37.9 L)
<b>DRIVE TRAIN</b>	Continuously Variable Transmission (CVT)	Continuously Variable Transmission (CVT)
<b>TRANSAXLE</b>	2/4WD Front, Selectable Locking Rear	2/4WD Front, Selectable Locking Rear
<b>GEAR SELECTION</b>	Mechanical, Steering Column Mounted	Mechanical, Steering Column Mounted
<b>FRONT/REAR AXLE RATIO</b>	3.1:1	3.1:1
<b>PERFORMANCE</b>		
<b>SEATING CAPACITY</b>	3 Person	3 Person
<b>CURB WEIGHT</b>	1,657 lb (751.6 kg)	1,608 lb (729.4 kg)
<b>BED LOAD CAPACITY</b>	1000 lb (453.6 kg)	1000 lb (453.6 kg)
<b>VEHICLE LOAD CAPACITY</b>	1500 lb (680.4 kg)	1500 lb (680.4 kg)
<b>SPEED</b>	25 mph (40.2 kph)	25 mph (40.2 kph)
<b>TOWING CAPACITY</b>	2000 lb (907.2 kg)	2000 lb (907.2 kg)
<b>OUTSIDE CLEARANCE CIRCLE</b>	29.5 ft.	29.5 ft
<b>STEERING &amp; SUSPENSION</b>		
<b>STEERING</b>	Rack and Pinion, Tilt Steering Wheel	
<b>FRONT SUSPENSION</b>	Double A-Arm with 10 in (25.4 cm) Travel	
<b>REAR SUSPENSION</b>	Double A-Arm with 9.5 in (24.1 cm) Travel	
<b>SERVICE BRAKE</b>	Dual Piston Front/Single Piston Rear Callipers	
<b>PARKING BRAKE</b>	Parking Gear, Activated Via Shifter	
<b>FRONT/REAR TIRES</b>	25 x 10.5 - 12 All Terrain	