



CUSHMAN®

TITAN® XD



MEET THE REAL INDUSTRY GIANT.

Equipped with AC and IntelliBrake™ technology, the Titan XD offers increased energy efficiency and greater range, ready to conquer your longest days. A large cargo deck offers 3,000 pounds of hauling power and its impressive 8,000 lb towing capacity makes no task off limits. So take the burden out of your day and let the Titan XD carry the load.

LET'S WORK.®

48V
AC ELECTRIC
POWERTRAIN

2 & 4
PASSENGER
MODELS

8000LB
TOWING
CAPACITY



2-PASSENGER



4-PASSENGER

CUSHMAN® TITAN® XD



HALOGEN HEADLIGHTS



FUNCTIONAL DASH

OPTIONAL TURN SIGNALS



OPTIONAL PINTLE HITCH

OPTIONS & ACCESSORIES

- Non-Marking Tires
- Front & Rear Bumper
- Hard Cab (w/ or w/out Doors)
- Pintle Hitch (requires rear bumper)
- Clevis Hitch (requires rear bumper)
- Custom Color
- Headlights (LED)
- Turn Signals

	2-PASSENGER	4-PASSENGER
BODY & CHASSIS		
FRAME	Welded Steel with DuraShield™ Powder Coat	
BODY & FINISH	Diamond Plate Patterned, Poly Primer & Acrylic	
STANDARD COLOR	Yellow	
DIMENSIONS		
OVERALL LENGTH	114.0 in (290 cm)	
OVERALL WIDTH	44.5 in (113 cm)	
OVERALL HEIGHT	47.0 in (119 cm)	
HEIGHT W/ OPTIONAL CAB	72.0 in (183 cm)	
WHEEL BASE	67.0 in (170 cm)	
FRONT WHEEL TRACK	38.0 in (96.0 cm)	
REAR WHEEL TRACK	38.0 in (96.0 cm)	
GROUND CLEARANCE	5.0 in (12 cm)	
CARGO DECK CAPACITY	41.5 in (105) W x 75 in (191 cm) L	4.75 (12.1 cm) at Differential
CARGO DECK MATERIAL	Weather Proof Deck Board	
POWER		
POWER SOURCE	48-Volt DC	
HORSEPOWER (KW)	16.8 HP (12.5 kW) Peak	
ELECTRICAL SYSTEM	48-Volt	
BATTERY (QTY/TYPE)	Eight, 6-Volt Deep Cycle, Swing Out	
BATTERY CHARGER	48V On-Board, 120/240 VAC UL	
KEY OR PEDAL START	Pedal Start	
SPEED CONTROLLER	450 Amp AC	
DRIVE TRAIN	Motor Shaft Direct Drive	
TRANSAXLE	Differential with Helical Gears	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse	
REAR AXLE RATIO	17:1	
PERFORMANCE		
SEATING CAPACITY	2-Person	4-Person
WEIGHT W/O BATTERIES	1260 lb (572 kg)	1225 lb (560 kg)
CURB WEIGHT	1756 lb (796 kg)	1720 lb (780 kg)
VEHICLE LOAD CAPACITY	3000 lb (1361 kg)	
CARGO DECK LOAD CAPACITY	2600 lb (1179 kg) / 1600 lb (726 kg) EE	2200 lb (998 kg) / 1200 lb (544 kg) EE
TOWING CAPACITY	8000 lb (3628 kg)	
OUTSIDE CLEARANCE CIRCLE	21.25 ft (6.47 m)	
INTERSECTING AISLE CLEARANCE	84.0 ft (213 cm)	
SPEED	14 mph +/- 0.5 mph (21 kph +/- 0.8 kph) / Tow Mode: 5 mph +/- .5 (8.1 kph +/- .8)	
STEERING & SUSPENSION		
STEERING	Rack and Pinion	
FRONT SUSPENSION	Independent, Transverse Leaf Spring, Shocks	
REAR SUSPENSION	Leaf Springs & Shock Absorbers	
SERVICE BRAKE	Front Hydraulic Disc, Rear Hydraulic Drum	
PARKING BRAKE	IntelliBrake™ Automatic Parking Brake	
FRONT/REAR TIRES	5.70 x 8 (Load Range C)	

www.cushman.com

©2018 Textron Specialized Vehicles Inc. All rights reserved.
800.241.5855

82324-G4 (Rev. 07/2018)